

**NONPROVISIONAL APPLICATION FOR LETTERS PATENT
UNITED STATES OF AMERICA**

5

Be it known that I, **RALPH M. THOMAS**, residing at **22 Bear Trail, Ellijay, Georgia 30540**, a citizen of the United States, have invented certain new and useful improvements in a

10

VEHICLE

15

of which the following is a specification.

20

INVENTOR'S REPRESENTATIVE

25

**JOEL D. MYERS, ESQ.
DUANE N. MOORE, ESQ.**

30

**MYERS & KAPLAN
INTELLECTUAL PROPERTY LAW, L.L.C.**

35

1827 Powers Ferry Road
Building 3, Suite 200
Atlanta, GA 30339
Telephone: (770) 541-7444
Facsimile: (770) 541-7448
Email: jmyers@mkiplaw.com

VEHICLE

5

TECHNICAL FIELD

The present invention relates generally to vehicles, and more specifically to a multi-wheel drive vehicle having independent hub motors, wherein each hub motor is
10 controlled by a single throttle, and wherein the vehicle is capable of alternating between multiple modes of operation.

BACKGROUND OF THE INVENTION

15 As off-road driving continues to increase in popularity, riders continually place higher demands on their vehicle's performance. Snow, sand, mud, rocks and other rough terrain demands the increased traction and mobility of multiple-drive vehicles. As off-road motors
20 become increasingly bigger and faster, having only one powered wheel subjects riders to extreme hazards, such as vehicle damage and/or personal injury. For professional riders, precious time is lost maneuvering around obstacles. Additionally, having only one powered rear wheel
25 burdensomely requires that the rider maintain his or her

weight on the rear wheel to preserve vehicle balance and improve overall off-road riding skills.

In an attempt to increase off-road vehicle
5 performance, many riders typically equip their vehicles
with large, wide, low-pressure rubber tires with an ample
amount of tread. By utilizing a tire with a wider base,
the surface area in contact with the ground is increased,
thereby distributing the vehicle's weight over a greater
10 area and allowing the vehicle to traverse over soft terrain
such as sand, snow and mud. Moreover, enlarging the
surface area in contact with the ground also results in
greater friction between the tire and the ground, thereby
increasing tire traction and overall vehicle performance.
15 However, despite the advantages of wide all-terrain tires,
most two-wheel vehicles, such as bicycles, mopeds and
scooters, utilize relatively thin, conventional road tires.
Due to the mechanical complexity of attaching a wheel that
is wider than the axle of the vehicle's pedals, most two-
20 wheel vehicles utilize wheels that are no wider than 2.5
inches, and thus, inherently fail to provide the advantages
of wide all-terrain tires.

Numerous motors and propulsion systems have also been developed to increase off-road vehicle performance. Historically, motors have often been large and of relatively heavy weight. However, in order to keep the overall size and weight of the vehicle as low as possible, it is desirable to have a small and lightweight motor. As such, hub motors have now been developed to provide a lightweight propulsion system that requires minimal space, wherein such hub motors are built into the hubs of the vehicle, thereby taking advantage of and occupying an empty or open area of the vehicle not previously utilized. Placing motors in the wheel hubs also provides the vehicle with a low center of gravity and an equal distribution of weight thereover. Such a configuration is especially advantageous when driving a two-wheel vehicle or when operating a vehicle on rough terrain.

Despite the advantages of multiple-drive vehicles, hub-motored vehicles typically utilize a single hub motor, as employing multiple hub motors usually requires multiple throttle controls. Furthermore, most motorized vehicles have only one mode of operation, either on or off, and are

not capable of alternating between hill-climbing, fuel efficient, and silent modes.

Therefore, it is readily apparent that there is a need
5 for an off-road vehicle with multiple-wheel drive, wherein power is supplied by compact, lightweight hub motors located in each wheel hub, and wherein the hub motors are collectively controlled by a single throttle. Furthermore, there is a need for an off-road vehicle capable of
10 alternating between multiple modes of operation, including hill-climbing, fuel efficient, and stealth modes.

BRIEF SUMMARY OF THE INVENTION

15 Briefly described, in a preferred embodiment, the present invention overcomes the above-mentioned disadvantages and meets the recognized need for such a device by providing a multi-wheel drive vehicle having hub motors positioned within each wheel hub, wherein the hub
20 motors are collectively controlled by a single throttle, and wherein the vehicle has multiple modes of operation, including hill-climbing, fuel efficient, and stealth modes.

According to its major aspects and broadly stated, the present invention in its preferred form is a multi-wheel drive vehicle having, in general, a frame, front wheel and rear wheels, pedal and drive assembly, throttle, and a
5 motor controller.

More specifically, the present invention is a multi-wheel drive vehicle wherein the wheels each possess a hub motor and a wide all-terrain tire. Preferably, the vehicle
10 can selectively change between motorized propulsion, as provided via the hub motors, manual propulsion, as provided via a manually driven pedal and drive assembly, or motor-assisted propulsion, as provided via the pedal and drive assembly and the hub motors. Should motorized propulsion
15 be selected, the pedal and drive assembly is preferably partially folded away.

Preferably, a single throttle jointly controls the speed of all hub motors. Additionally, a motor controller
20 protects the hub motors from over-current and over-heating, and further preferably enables the vehicle to alternate between various modes of operation and configurations of performance via selective regulation of the hub motors.

Accordingly, a feature and advantage of the present invention is its ability to alternate between various modes and configurations of performance.

5 Another feature and advantage of the present invention is its ability to alternate between motorized, manually-powered, and motor-assisted propulsion.

10 Another feature and advantage of the present invention is its ability to move the pedal and drive assembly into a partially folded position when motorized propulsion is selected.

15 Another feature and advantage of the present invention is its ability to operate under minimal power requirements due to the vehicle's compact size and light weight.

20 Another feature and advantage of the present invention is its multi-wheel drive capabilities utilizing multiple independent hub motors.

Another feature and advantage of the present invention is its ability to control multiple motors with a single throttle.

5 Another feature and advantage of the present invention is its use of wide all-terrain tires for better traction and increased vehicle performance.

Another feature and advantage of the present invention
10 is its ease of use.

These and other features and advantages of the present invention will become more apparent to one skilled in the art from the following description and claims when read in
15 light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The present invention will be better understood by reading the Detailed Description of the Preferred and Selected Alternate Embodiments with reference to the accompanying drawing figures, in which like reference

numerals denote similar structure and refer to like elements throughout, and in which:

FIG. 1 is a perspective view of a vehicle according to
5 a preferred embodiment of the present invention.

FIG. 2 is a partial cross-sectional view of a wheel assembly according to a preferred embodiment of the present invention.

10

FIG. 2A is a side view of a hub motor according to a preferred embodiment of the present invention.

FIG. 3 is a schematic illustration of the program flow
15 of a motor controller according to a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED AND SELECTED

ALTERNATIVE EMBODIMENTS

20

In describing the preferred and selected alternate embodiments of the present invention, as illustrated in **FIGS. 1-3**, specific terminology is employed for the sake of

clarity. The invention, however, is not intended to be limited to the specific terminology so selected, and it is to be understood that each specific element includes all technical equivalents that operate in a similar manner to
5 accomplish similar functions.

Referring now to **FIGS. 1-3**, the present invention in a preferred embodiment is a vehicle **10** generally preferably possessing frame **120**, front wheel assembly **220**, rear wheel
10 assembly **320**, pedal and drive assembly **420**, brakes **520**, throttle **620**, and motor controller **720**. Although the preferred embodiment of vehicle **10** is in the form of a bicycle, it is contemplated in an alternative embodiment that vehicle **10** could be in the form of other vehicles,
15 such as, for exemplary purposes only, mopeds, scooters, motorcycles, tricycles, four-wheelers, and the like.

Referring now more specifically to **FIG. 1**, frame **120** is preferably a conventional bicycle-type frame wherein
20 front fork **130** is preferably steerably mounted on front portion **122** of frame **120** for steering vehicle **10**. Preferably, front wheel assembly **220** is rotatably mounted on bottom portion **140** of front fork **130**, and rear wheel

assembly **320** is rotatably mounted on rear portion **150** of frame **120**. As more fully described below, in order to equip vehicle **10** with all-terrain tires, bottom portion **140** and rear portion **150** are preferably configured and dimensioned to accommodate tires as wide as 7 inches; however, it should be recognized that bottom portion **140** and rear portion **150** could be dimensioned to accommodate any size and width of tire. Although it is preferred that vehicle **10** comprise front wheel assembly **220** and rear wheel assembly **320**, it is contemplated in an alternate embodiment that vehicle **10** could comprise any suitable number of front and/or rear wheel assemblies. Preferably, frame **120** also includes seat **160**, adjustably mounted to top portion **162** of frame **120**, wherein includes seat **160**, preferably functions to support the rider of vehicle **10**. Handlebars **170** are preferably connected to top portion **172** of front fork **130** for allowing the rider to steer the vehicle in a selected direction. Additionally, preferably disposed on bottom portion **422** of frame **120** is pedal and drive assembly **420** for manually powering vehicle **10**, as more fully described below.

Referring now to **FIGS. 2-2A**, and with continued reference to **FIG. 1**, front wheel assembly **220** preferably comprises tire supporting rim **230**, hub motor **240** and tire **250**. Hub motor **240** is preferably a small, compact, conventional electric hub motor known with the art, wherein hub motor **240** is preferably mounted inside tire supporting rim **230** of front wheel assembly **220** via any suitable mounting means known within the art, such as, for exemplary purposes only, rivets, bolts, welding, and the like. It is contemplated that hub motor **240** could alternatively embody other suitable motors, so long as hub motor **240** functions to provide a torque force sufficient to rotationally drive supporting rim **230** of front wheel assembly **220** to propel vehicle **10** in a forward or reverse direction. Furthermore, hub motor **240** preferably possesses plastic gears for reducing the sound generated by the motor, as more fully described below.

Tire **250** is preferably a wide, low pressure, conventional all-terrain tire known with the art; however, it is contemplated in an alternative embodiment that any sized tire could be utilized. Preferably, tire **250** is mounted on tire supporting rim **230** of front wheel assembly

220, wherein tire 250 is formed from rubber and possesses an approximate width of 6 to 7 inches; however, it is contemplated in an alternative embodiment that tire 250 could be formed from any other suitable material and/or
5 possess any desired width.

As further illustrated in **FIGS. 2-2A**, rear wheel assembly 320 preferably comprises tire supporting rim 330, hub motor 340 and tire 350; wherein tire supporting rim 330
10 is substantially identical to tire supporting rim 230, and wherein tire 350 is substantially identical to tire 250. Hub motor 340 is preferably substantially identical to hub motor 240, wherein hub motor 340 preferably utilizes metal gears to assist rear wheel assembly 320 in a hill-climbing
15 mode, as more fully described below. Preferably, front wheel assembly 220 and rear wheel assembly 320 are substantially equal in size and dimension; however, it is contemplated in an alternate embodiment that front wheel assembly 220 and rear wheel assembly 320 could differ in
20 size and dimension.

As an alternative to electric propulsion via hub motor 340, rear wheel assembly 320 could preferably be propelled

by manual human-power. Preferably attached to the side of rear wheel assembly **320** is manual drive mechanism **470**, wherein manual drive mechanism **470**, in conjunction with pedal and drive assembly **420**, preferably propels rear wheel assembly **320** via human pedal-power, as more fully described below. Although it is preferred that manual drive mechanism **470** be bolted to rear wheel assembly **320**, it is contemplated in an alternate embodiment that any suitable attachment means known within the art be utilized, such as, for exemplary purposes only, rivets, machine screws, welding, and the like.

Pedal and drive assembly **420** preferably includes pedals **430**, crank arms **440**, pedal gear **450**, chain **460** and manual drive mechanism **470**, wherein pedal gear **450** is preferably rotatably mounted on bottom portion **422** of frame **120**. Additionally, pedals **430** are preferably rotatably mounted to first end **442** of crank arm **440**, wherein second end **444** of crank arm **440** is preferably permanently centrally affixed to pedal gear **450**. Furthermore, first end **462** of chain **460** is preferably mounted around pedal gear **450**, wherein second end **464** of chain **460** is preferably mounted around manual drive mechanism **470**, and, as such,

preferably results in chain **460** forming a continuous loop around pedal gear **450** and manual drive mechanism **470**. Preferably, manual rotational movement of pedals **430** and crank arms **440** turns pedal gear **450** and moves chain **460**
5 under and around manual drive mechanism **470**, thereby rotating manual drive mechanism **470** and propelling rear wheel assembly **320** in a forward direction.

Crank arms **440** preferably possess hinges **442A** for
10 enabling the folding away of crank arms **440** and pedals **430** when not in use. Moreover, crank arms **440** preferably possess locking mechanisms **444A** to securely maintain crank arms **440** and pedals **430** in a folded position, wherein locking mechanisms **444A** are any suitable locking means,
15 such as, for exemplary purposes only, straps, fasteners, screw locks, cam locks, stops, detents or the like. Furthermore, although hinges **442A** are preferably utilized to hingably fold away crank arms **440** when not in use, it is contemplated in an alternate embodiment that other means of
20 moving pedals **430** and crank arms **440** could be employed, such as, for exemplary purposes only, foldable pedals hinged at their point of connection with the crank arm, foldable crank arms hinged at their point of connection

with the pedal gear, telescoping and retractable pedals and crank arms, removable pedals and crank arms, and/or removable pedals and/or crank arms.

5 Brakes **520** is preferably a conventional apparatus and system that allows the rider to reduce the speed of the vehicle, as is well known to those skilled in the art. Although it is preferred that brakes **520** be a cable pull system, it is contemplated in an alternate embodiment that
10 brakes **520** could embody other suitable brake systems, such as, for exemplary purposes only, hydraulic or pneumatic brakes, pedal brakes, and the like. Specifically, brakes **520** preferably include brake controls **530**, brake cable **540** and hub brakes **550**, wherein brake controls **530** are brake
15 levers disposed on handle bars **170**. Although hub brake **550** is preferably mounted on each tire supporting rim **230** and **330**, it is contemplated in an alternate embodiment that any number of hub brakes **550** could be utilized, such as, for exemplary purposes only, a single hub brake **550** mounted on
20 tire supporting rim **330**. Preferably, brake cable **540** is utilized to actuate hub brakes **550** via hand operation and engagement of brake controls **530**.

Preferably, vehicle **10** further possesses throttle **620**, wherein throttle **620** permits the rider to control the speed of the vehicle. Preferably, throttle **620** sends a signal to motor controller **720**, wherein motor controller **720** controls the voltage and current available to hub motors **240** and **340**, as more fully described below. Throttle **620** is preferably a cable pull system; however, it is contemplated in an alternate embodiment that throttle **620** could embody other suitable known throttle systems, such as, for exemplary purposes only, potentiometers or hall effect sensors, so long as the selected throttle jointly controls both hub motor **240** and hub motor **340**. Preferably, throttle **620** possesses throttle control **630**, wherein throttle control **630** is disposed on handle bars **170**. Preferably, throttle control **630** is a twist grip throttle; however, it is contemplated in an alternate embodiment that throttle control **630** could embody other suitable known throttle controls, such as, for exemplary purposes only, thumb throttles, lever throttles, or switch throttles, so long as throttle control **630** is capable of jointly controlling both hub motor **240** and hub motor **340**.

Preferably, vehicle **10** further possesses motor controller **720**, wherein motor controller **720** preferably controls the voltage and current available to hub motors **240** and **340**, thus controlling the power and speed thereof, as known within the art. Preferably, motor controller **720** comprises microchip **730**, wherein microchip **730** is programmable for effectuating various modes and configurations of performance, and wherein microchip **730** protects hub motors **240** and **340** from over-current and over-heating. Additionally, vehicle **10** preferably possesses power source **732**, preferably in the form of a battery or other similar transportable power source, wherein power source **732** preferably supplies the requisite operational power for hub motors **240** and **340**.

Preferably, microchip **730** can further be programmed to accept instructions from the rider via throttle **620** and/or selector switch **740**, wherein throttle **620** jointly controls the power and speed of hub motors **240** and **340**, and wherein selector switch **740** is a user interface that alternates controller **720** between various modes of operation, as more fully describe below. Selector switch **740** is preferably a lever switch disposed on handle bars **170**; however, it is

contemplated in an alternate embodiment that selector switch **740** could embody other suitable switch mechanisms accessible to the rider, such as, for exemplary purposes only, thumb switches, joystick switches, grip handle
5 switches, or the like.

In a preferred embodiment, motor controller **720** is capable of switching between normal mode, wherein equal power is available to hub motor **240** and hub motor **340**;
10 hill-climbing mode, wherein all power is sent to hub motor **340**; stealth mode, wherein all power is sent to hub motor **240**; and, fuel efficient mode, wherein power allocation is configured by microchip **730** for maximum performance. When in stealth mode, vehicle **10** is configured for minimal
15 noise, as the louder metal gears of hub motor **340** are preferably deactivated, and wherein the silent plastic gears of hub motor **240** are preferably activated. Stealth mode may be particularly important when vehicle **10** is driven off road for hunting activities, as animals will
20 typically flee from otherwise loud engine noise. It is recognized that motor controller **720** could be capable of alternating between other useful modes of operation, such as, for exemplary purposes only, hill-descending mode,

enhanced speed modes, turbo modes, idle mode, and/or the like.

As previously discussed, although the preferred
5 embodiment of vehicle **10** is in the form of a bicycle, it is contemplated in an alternative embodiment that vehicle **10** could embody other vehicles such as mopeds, scooters, motorcycles, tricycles and/or four-wheelers.

10 In another alternate embodiment, vehicle **10** could have any suitable number of front wheel assemblies **220** and any number of rear wheel assemblies **320**.

In another alternate embodiment, front wheel assembly
15 **220** and rear wheel assemblies **320** could differ in size, dimension, power, tire size, torque, etc.

In another alternate embodiment, vehicle **10** could have any number of seats **160**.

20

In another alternate embodiment, vehicle **10** could have multiple sets of pedals **430**, or eliminate pedal and drive assembly **420** entirely.

In another alternate embodiment, vehicle **10** could utilize conventional road tires instead of all-terrain tires **250**.

5 In another alternate embodiment, handle bars **170** could be replaced by a steering wheel or a joystick.

In still another alternate embodiment, vehicle **10** could possess shocks.

10

In yet another alternate embodiment, vehicle **10** could possess any number of headlights, taillights and turn-signals.

15 In still another alternate embodiment, vehicle **10** could possess a sidecar and/or rear buggy.

Having thus described exemplary embodiments of the present invention, it should be noted by those skilled in
20 the art that the within disclosures are exemplary only, and that various other alternatives, adaptations, and modifications may be made within the scope of the present

invention. Accordingly, the present invention is not limited to the specific embodiments illustrated herein, but is limited only by the following claims.